

## ANUChrome – LEMON Chrome L-26

ANUChrome L-26 is a monoclinic lead chromate and is a raw material for the Paint industry. This is an economical grade in Lemon Chromes product range. This pigment is stabilized one and it generally offers good fastness to light and weather. This pigment has fair dispersion characteristics.

### TECHNICAL DATA

Colour Index No.	77603
Colour Index Pigment No.	Y-34
Oil Absorption	16-21
Specific Gravity	4.9-6.0
Bulk Density g/cc	1.03
<b>BLEEDING IN (1-Poor 5-Excellent)</b>	
Water	5
5% Caustic Soda	3
5% Hydrochloric Acid	3
Linseed Oil	5
Ethanol	5
Ethyl Acetate	5
Xylene	5
n-Butanol	5
Methyl Ethyl Ketone	5
Mineral Turpentine	5
Cellosolve	5
Diocetyl Phthalate	5
<b>RESISTANCE TO HEAT</b>	
120°C / 30 min.	SB
150°C / 20 min.	SB
180°C / 10 min.	SB
210°C / 10 min.	SB
<b>RESISTANCE TO LIGHT</b>	
Full Tone	4
Tint Tone (1:10)	5
<b>RESISTANCE TO</b>	
Acid	G
Alkali	P
<b>APPLICATIONS</b>	
Paints	*
Printing Inks	*
Rubber	
Leather Pastes	*
Linoleum	*
PVC Leather Cloth	*
Paper Coating	*

Chalk / Crayons	
Plastics	*

### LEGEND

COLOUR	BLEEDING	HEAT STABILITY	LIGHTFASTNESS	APPLICATIONS	
Y – YELLOW	SCALE (1-5)	SB : STABLE	SCALE (1-8)	* :RECOMMENDED/	<b>E</b> – EXCELLENT
R – RED	5:NO BLEED	USB : UNSTABLE	1 – POOR	MAYBE USED	<b>VG</b> – VERY GOOD
W – WHITE	1:CONSIDERABLE BLEED		8 – EXCELLENT		<b>G</b> – GOOD
					<b>F</b> – FAIR
					<b>P</b> – POOR