

ANUCRYL CP-180

INTRODUCTION:

ANUCRYL CP-180 is the outcome of extensive research carried out by our R & D. It has been engineered to provide high-grade exterior emulsion paint having resistance to dirt.

APPLICATION:

ANUCRYL CP-180 can be used in making high quality & durable paint for external surfaces. Due to resistance to dirt pick-up, the paint surfaces do not look dirty in tropical weather. The paint has good resistance to hydrolysis as well. **ANUCRYL CP-180** can be used in paint formulation having varied PVC levels.

TYPICAL PROPERTIES

Appearance	Milky white liquid
Total solids (at 150°C for half an hour) %	50 ± 1 8.7 - 9.1
pH (as is)	500-1000 cps.
Brookfield viscosity LVT on spindle # 3 & 60rpm @ 25°C, CPS	1.06- 1.08
Specific Gravity at 30° C	Anionic Surfactant
Stabilisation	

SAFETY DATA

HEALTH HAZARDS: **ANUCRYL CP-180** is alkaline in nature and harmful if swallowed. Avoid skin contact. Use protective clothings, hand gloves, goggles etc. while handling. In case of contact, splash on eyes, wash with plenty of water and consult a physician.

FIRE HAZARDS: **ANUCRYL CP-180** is non-flammable.